

TECHNICAL DATA

Scapa 2724

PVC Hazard Warning Adhesive Tape

DESCRIPTION

Scapa 2724 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubber-based adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability. Available in striped colours only.

APPLICATIONS

- Hazard warning and safety tape
- Identification of potential danger areas

PRODUCT BENEFITS

- Excellent resistance to abrasion, corrosion, and moisture
- Suitable for indoor and protected outdoor environments
- High abrasion and mechanical resistance
- Excellent conformability
- Easy transversal tearability
- Environmentally friendly technology
- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)

lssue: 3 Date: 15/09/08 Page 1 of 2 2724.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

	Unit	Value	Test Method
Nominal Thickness	mm	0,16	CEI EN 60454
Tensile Strength	N/cm	25	CEI EN 60454
Elongation at Break	%	150	CEI EN 60454
Adhesion to Steel	N/cm	1.5	CEI EN 60454
Adhesion to Backing	N/cm	1.5	CEI EN 60454

STANDARD PRESENTATION

Roll length: 33 metres

Roll width: 50, 75 and 100mm

Core: 76mm Scapa branded cardboard core

Packaging: Heat shrink sleeve

Colours: (Striped) Yellow/black, White/red

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between $+10^{\circ}$ c and $+25^{\circ}$ c. Use within 24 months of receipt.

The tape should be applied with sufficient pressure t o ensure optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

lssue: 3 Date: 15/09/08 Page 2 of 2 2724.doc

www.scapa.com